



FEATURES

- Advanced Technology Energy Efficient LEDs
- Up to 28,500 Lumens (170 Watt)
- Outdoor IP67 Rated
- I/O Port Sync with Sensors, Devices
- Automatic Day/Night Sensor
- PoE++ Option: 75 Watt
- Lifetime Warranty, Made in the USA

SPECIFICATIONS

Wavelength	White Light/ Temp. 6000K
Lumens	170W: 28,500Lm / 75W: 12,600Lm
Input Voltage Options	24 to 36VDC
	Universal AC
	PoE++ 802.3bt (75W Only)
Power Consumption	Options: 75W or 170 Watts
Operating Temp.	-58° to 140°F / -50° to 60°C
Dimensions	23.78" x 7.3" x 15.2" varies
Weight	15 - 28 lbs / varies by model
Environmental	Outdoor IP67 Rated
Mounting	Pan/Tilt Mounting System*

*Pole, Wall or Corner Mount Required (depending upon mounting location)



Blaze 180 Long Range White LED Floodlight

Optimize scene lighting by adjusting the panels to increase or decrease the range or the HFOV (Horizontal Field of View). For maximum 180° coverage keep the lights rotated all the way outward. Rotate the lights inward to increase the range and reduce the HFOV.


Easy Integration & Control


Seamless and precise control via Input/Output ports. Sync with camera, sensors or other system devices with I/O ports. For easy integration, a built-in photocell switches the IR ON/OFF based on lighting conditions.

RANGE 180° HFOV

170 Watt Range: 462ft /140m


75 Watt Range: 308ft /93m






RANGE







Made in the USA

Other lens angles/ranges are available with ranges up to 2,075ft, contact us for details.

801 Robinson Drive, Suite #500, North Salt Lake, UT 84054 Tel: 801/519-0500 • Email: sales@axtontech.com • Website: axtontech.com

°AXTON JAN 2023.B

